

# TECHNICAL DATA SHEET



Type no.	AGM 710 01	
Article no.	016710010101	
EAN/GTIN no.	9005753098886	
Application	Starter battery	
<b>Electrical data</b>		
Rated voltage	12V	
Rated capacity	210 Ah (K20)	
Cold start current	1200 A (EN)	
<b>Dimensions and weights</b>		
Box	C	
Length max.	517mm	
Width max.	273mm	
Box height max.	212mm	
Total height max.	240mm	
Battery weight	Ca. 62,0 kg (+/- 5 %)	
Electrolyte density	Approx. 1,32 kg/l	
Electrolyte	Diluted sulphuric acid	
Items/pallet	18	
Pallet ID	Euro pallet	
Items per layer	6	
		
<b>Features</b>		
Base hold-down	B00	
Layout	3	
Terminal	1	
Separator	AGM separator	
Degassing	Battery with central degassing	
Flame arrester	Integrated	
Performance identification	W5 - C2 - V3+ - M3 (E4)	
<b>Maintenance 1)</b>		
Water consumption	W5	
Refill water	Absolutely maintenance-free	
Self-discharge	Approx. 3 % per month	
Charging current	Approx. 1/20 of the rated capacity	
Charging voltage 2)	max. 14,8 V	

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2021-05-06; Rights relating to changes and errors retained.  
original